



MFTN138 N-Channel Logic Level Enhancement Mode Field Effect Transistor

for low voltage, low current switching applications



1. Gate 2. Source 3. Drain
SOT-23 Plastic Package



Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	50	V
Drain-Gate Voltage ($R_{GS} \leq 20 \text{ k}\Omega$)	V_{DGR}	50	V
Gate-Source Voltage - Continuous	V_{GSS}	± 20	V
Gate-Source Voltage - Non-Repetitive ($T_P < 50 \mu\text{s}$)		± 40	
Drain Current - Continuous	I_D	220	mA
Drain Current - Pulsed		880	
Total Power Dissipation	P_{tot}	360	mW
Operating and Storage Temperature Range	T_j, T_s	- 55 to + 150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	347	K/W

Characteristics at $T_a = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Min.	Max.	Unit
Drain-Source Breakdown Voltage at $I_D = 250 \mu\text{A}$	$V_{(\text{BR})\text{DSS}}$	50	-	V
Drain-Source Leakage Current at $V_{DS} = 50 \text{ V}$ at $V_{DS} = 30 \text{ V}$	I_{DSS}	- -	500 100	nA
Gate-Source Leakage Current at $V_{GS} = \pm 20 \text{ V}$	I_{GSS}	-	± 100	nA
Gate-Source Threshold Voltage at $V_{GS} = V_{DS}, I_D = 1 \text{ mA}$	$V_{GS(\text{th})}$	0.8	1.6	V
Drain-Source On-State Resistance at $V_{GS} = 10 \text{ V}, I_D = 220 \text{ mA}$ at $V_{GS} = 4.5 \text{ V}, I_D = 220 \text{ mA}$	$R_{DS(\text{on})}$	- -	3.5 6	Ω
Forward Transconductance at $V_{DS} = 10 \text{ V}, I_D = 220 \text{ mA}$	g_{FS}	0.12	-	S
Input Capacitance at $V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{iss}	-	60	pF
Output Capacitance at $V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{oss}	-	25	pF
Reverse Transfer Capacitance at $V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{rss}	-	10	pF
Turn-On Delay Time at $V_{DD} = 30 \text{ V}, I_D = 290 \text{ mA}, V_{GS} = 10 \text{ V}, R_G = 50 \Omega$	$t_{d(on)}$	-	8	ns
Turn-On Rise Time at $V_{DD} = 30 \text{ V}, I_D = 290 \text{ mA}, V_{GS} = 10 \text{ V}, R_G = 50 \Omega$	t_r	-	12	ns
Turn-Off Delay Time at $V_{DD} = 30 \text{ V}, I_D = 290 \text{ mA}, V_{GS} = 10 \text{ V}, R_G = 50 \Omega$	$t_{d(off)}$	-	16	ns
Turn-Off Fall Time at $V_{DD} = 30 \text{ V}, I_D = 290 \text{ mA}, V_{GS} = 10 \text{ V}, R_G = 50 \Omega$	t_f	-	22	ns


Drain-Source Diode Characteristics and Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Maximum Continuous Source Current	I_S	-	220	mA
Maximum Pulse Source Current	I_{SM}	-	880	mA
Drain-Source Diode Forward Voltage at $I_S = 440 \text{ mA}$	V_{GD}	-	1.4	V

PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT-23



UNIT	A	B	b_p	C	D	E	H_E	A_1	L_p
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20